# SAFETY DATA SHEET



# 1. PRODUCT

## **1.1 Product identifiers**

Name: Acetic acid

CAS-No.: 64-19-7

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

# GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H226

Skin corrosion (Category 1A), H314

Serious eye damage (Category 1), H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Company

China Amines Co., Ltd UNIT 1021, BEVERLEY COMMERCIAL CENTRE, 87-105CHATHAM ROAD SOUTH, TSIM SHA TSUI, KOWLOON HONG KONG

Telephone: +86 18938922889 e-mail: info@chinaamines.com Website: www.chinaaminescom

Pictogram	
Signal word	Danger
Hazard statement(s)	H226 Flammable liquid and vapour. H314 Causes severe skin burns and eye damage.
Precautionary statement(s)	<ul> <li>P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.</li> <li>P233 Keep container tightly closed.</li> <li>P240 Ground/bond container and receiving equipment.</li> <li>P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.</li> <li>P242 Use only non-sparking tools.</li> <li>P243 Take precautionary measures against static discharge.</li> <li>P264 Wash skin thoroughly after handling.</li> <li>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</li> <li>P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</li> <li>P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.</li> <li>P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.</li> <li>P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P310 Immediately call a POISON CENTER/doctor.</li> <li>P321 Specific treatment (see supplemental first aid instructions on this label).</li> <li>P363 Wash contaminated clothing before reuse.</li> <li>P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.</li> <li>P403 + P235 Store in a well-ventilated place. Keep cool.</li> <li>P405 Store locked up.</li> <li>P501 Dispose of contents/ container to an approved waste disposal plant.</li> </ul>

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

No data available

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

Synonyms: Gl

## Hazardous components

Component	Classification	Concentration
Acetic acid		
	Flam. Liq. 3; Skin Corr. 1A; Eye Dam. 1; H226, H314, H318	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

## In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.Continue rinsing eyes during transport to hospital.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

## 4.2 Indication of any immediate medical attention and special treatment needed

No data available

# **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

#### 5.2 Special hazards arising from the substance or mixture

No data available

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

## 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all

sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive

concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

## 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in

container for disposal according to local regulations (see section 13).

## 6.4 Reference to other sections

For disposal see section 13.

## 7. HANDLING AND STORAGE

## 7.1 Precautions for safe handling

Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully

resealed and kept upright to prevent leakage.

# 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters

## Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis	
Acetic acid	64-19-7	TWA	10.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)	
	Remarks	Pulmonary function Upper Respiratory Tract irritation Eye irritation			
		STEL	15.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)	
		Pulmonary fund	ction Upper Resp	iratory Tract irritation	
		Eye irritation			
		ST 15.000000	opm 37.000000 r	ng/m3 USA. NIOSH Recommended Exposure Limits	
		Can be found ir	n concentrations	of 5-8% in vinegar	
e conce	TWA 10.000000 USA. NIOSH Recommended Exp ppm 25.000000 mg/m3		USA. NIOSH Recommended Exposure Limits		
		Can be found in concentrations of 5-8% in vinegar		of 5-8% in vinegar	
chenne		TWA	10.000000 USA. Occupational Exposure Limits (OSHA) -T ppm 25.000000 mg/m3		
		The value in mg/m3 is approximate.			
		TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)	
	Pulmonary function Upper Respiratory Tract irritation Eye irritation STEL 15 ppm USA. ACGIH Threshold Limit V		iratory Tract irritation Eye irritation		
			USA. ACGIH Threshold Limit Values (TLV)		
Pulmonary function Upper Respiratory Tract irritation Eye irritation			iratory Tract irritation Eye irritation		

Component	CAS-No.	Value	Control parameters	Basis
61 C	/	TWA	10 ppm 25 mg/m3	USA. NIOSH Recommended Exposure Limits
		Can be found ir	concentrations	of 5-8% in vinegar
and the second		ST	15 ppm 37 USA. NIOSH Recommended Exposure Limits	
		Can be found in concentrations of 5-8% in vinegar		
		TWA	10 ppm 25 mg/m3USA. Occupational Exposure Limits (OSHA) -Table Z-1 Limits for Air Contaminants	
		The value in mg/m3 is approximate.		
		PEL	10 ppm 25 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
		STEL	15 ppm 37 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		С	40 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

## 8.2 Exposure controls

# Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of

workday.

# Personal protective equipment

Eye/face protection	Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
Skin protection	Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Full contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M) Splash contact Material: Nature latex/chloroprene Minimum layer thickness: 0.6 mm Break through time: 32 min Material tested:Lapren® (KCL 706 / Aldrich Z677558, Size M) data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.
Body Protection	Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Respiratory protection	Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).
Control of environmen tal exposure	Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties

Appearance	Form: liquid Colour: colourless
Odour	pungent
Odour Threshold	No data available
рН	2.4 at 60.05 g/l
Melting point/freezing point	Melting point/range: 16.2 °C (61.2 °F) - lit.
Initial boiling point and boiling range	117 - 118 °C (243 - 244 °F) - lit. 117 - 118 °C (243 - 244 °F)

Flash point	No data available
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	Upper explosion limit: 19.9 %(V) Lower explosion limit: 4 %(V)
Vapour pressure	73.3 hPa (55.0 mmHg) at 50.0 °C (122.0 °F) 15.2 hPa (11.4 mmHg) at 20.0 °C (68.0 °F)
Vapour density	No data available
Relative density	1.049 g/mL at 25 °C (77 °F)
Water solubility	completely miscible
Partition coefficient: n-octanol/water	log Pow: -0.17
Auto-ignition temperature	485.0 °C (905.0 °F)
Decomposition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidizing properties	No data available

## 9.2 Other safety information

Surface tension: 28.8 mN/m at 10.0 °C (50.0 °F)

## **10. STABILITY AND REACTIVITY**

## 10.1 Reactivity

No data available

#### **10.2 Chemical stability**

Stable under recommended storage conditions.

#### 10.3 Possibility of hazardous reactions

No data available

## 10.4 Conditions to avoid

Heat, flames and sparks.

## 10.5 Incompatible materials

Oxidizing agents, Soluble carbonates and phosphates, Hydroxides, Metals, Peroxides, permanganates, e.g. potassium

permanganate, Amines, Alcohols, Nitric acid

#### **10.6 Hazardous decomposition products**

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

## 11.1 Information on toxicological effects

Acute toxicity
LD50 Oral - Rat - 3,310 mg/kg LC50 Inhalation - Mouse - 1 h - 5620 ppm Remarks: Sense Organs and Special Senses (Nose, Eye, Ear, and Taste):Eye:Conjunctive irritation. Sense Organs and Special Senses (Nose, Eye, Ear, and Taste):Eye:Other. Blood:Other changes. LC50 Inhalation - Rat - 4 h - 11.4 mg/l LD50 Dermal - Rabbit - 1,112 mg/kg No data available
Skin corrosion/irritation
Skin - Rabbit Result: Causes severe burns.

## Serious eye damage/eye irritation

Eyes - Rabbit Result: Corrosive to eyes

# Respiratory or skin sensitisation

#### No data available

#### Germ cell mutagenicity

No data available

## Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. **Reproductive toxicity** No data available

No data available

#### Specific target organ toxicity -single exposure

No data available

#### Specific target organ toxicity -repeated exposure

No data available

## **Aspiration hazard**

No data available

#### **Additional Information**

#### RTECS: AF1225000

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, Ingestion or inhalation of concentrated acetic acid causes damage to tissues of the respiratory and digestive tracts. Symptoms include: hematemesis, bloody diarrhea, edema and/or perforation of the esophagus and pylorus, pancreatitis, hematuria, anuria, uremia, albuminuria, hemolysis, convulsions, bronchitis, pulmonary edema, pneumonia, cardiovascular collapse, shock, and death. Direct contact or exposure to high concentrations of vapor with skin or eyes can cause: erythema, blisters, tissue destruction with slow healing, skin blackening, hyperkeratosis, fissures, corneal erosion, opacification, iritis, conjunctivitis, and possible blindness., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

## **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to fish       semi-static test LC50 - Oncorhynchus mykiss (rainbow trout) - > 1,000 mg/l - 96 h         (OECD Test Guideline 203)	
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - > 300.82 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae	No data available
Toxicity to bacteria	No data available

#### 12.2 Persistence and degradability

	aerobic - Exposure time 30 d Result: 99 % - Readily biodegradable Remarks: Expected to be biodegradable
Biochemical Oxygen Demand (BOD)	880 mg/g

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

## 12.6 Other adverse effects

Additional ecological information:

No data available

## **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### Contaminated packaging

Dispose of as unused product.

## **14. TRANSPORT INFORMATION**

## DOT (US)

UN number: 2789 Class: 8 (3) Packing group: II

Proper shipping name: Acetic acid, glacial

Reportable Quantity (RQ): 5000 lbs

Poison Inhalation Hazard: No

## IMDG

UN number: 2789 Class: 8 (3) Packing group: II EMS-No: F-E, S-C

Proper shipping name: ACETIC ACID, GLACIAL

## ΙΑΤΑ

UN number: 2789 Class: 8 (3) Packing group: II

Proper shipping name: Acetic acid, glacial

## **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De

Minimis) reporting levels established by SARA Title III, Section 313.

## SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### **Massachusetts Right To Know Components**

Component	CAS-No.	Revision Date
Acetic acid	64-19-7	1993-04-24

#### Pennsylvania Right To Know Components

Component	CAS-No.	<b>Revision Date</b>
Acetic acid	64-19-7	1993-04-24

#### New Jersey Right To Know Components

Component	CAS-No.	Revision Date
Acetic acid	64-19-7	1993-04-24

# California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other

reproductive harm.

## **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

Eye Dam. Serious eye damage

Flam. Liq. Flammable liquids

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

Skin Corr. Skin corrosion

# **HMIS Rating**

Health hazard: 3

Chronic Health Hazard: \*

Flammability: 2

Physical Hazard 0

# **NFPA** Rating

Health hazard: 3

Fire Hazard: 2

Reactivity Hazard: 0